

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Canceled).
- 1 2. (Previously presented) A universal collar that attaches to a pump and, in
2 turn, a container used in a dispenser having a keyplate, the universal collar
3 comprising:
4 a body having a first flange and a second flange, wherein said flanges
5 extend outward and are axially spaced from each other for receiving the
6 keyplate therebetween, wherein said flanges are connected on a forward
7 side of the universal collar by a vertically extending rib.
- 1 3. (Previously presented) A universal collar that attaches to a pump and, in
2 turn, a container used in a dispenser having a keyplate, the universal collar
3 comprising:
4 a body having a first flange and a second flange, wherein said flanges
5 extend outward and are axially spaced from each other for receiving the
6 keyplate therebetween, wherein at least one of said flanges defines a notch
7 on a rearward side thereof for receiving a projecting portion of the
8 dispenser.
- 1 4. (Original) The universal collar of Claim 3, wherein said notch is centered
2 within said flange on said rearward side.

- 1 5. (Previously presented) A universal collar that attaches to a pump and, in
2 turn, a container used in a dispenser having a keyplate, the universal collar
3 comprising:
4 a body having a first flange and a second flange, wherein said flanges
5 extend outward and are axially spaced from each other for receiving the
6 keyplate therebetween, wherein said body includes a top edge, said top
7 edge defining a locating recess for receipt of a projection on the container,
8 said recess having a base and a pair of upstanding sides, wherein said sides
9 are circumferentially spaced from each other for receipt of the projection
10 therebetween.
- 1 6. (Original) The universal collar of Claim 5, wherein one of said sides extends
2 perpendicular to said base and the other of said sides extends obliquely
3 relative to said base.
- 1 7. (Original) The universal collar of Claim 5, wherein said top edge extends
2 axially upward relative to said first flange and extends in a circular fashion
3 to circumscribe a portion of the container.
8. (Canceled).
- 1 9. (Previously presented) A universal collar comprising a hollow cylindrical
2 collar having a first flange and a second flange extending at least
3 rearwardly therefrom, and axially spaced to define a receiver clearance
4 therebetween, wherein said flanges extend radially outward from said
5 collar, each flange defining a notch that opens rearwardly relative to said
6 collar.
10. (Canceled).
11. (Canceled).